



THERMOPLAST™ DECORATIVE FACING FOIL (990)

Introduction

Bradford Thermoplast™ Decorative Facing Foil (990) is a premium medium duty reflective facing foil with a decorative white finish on one side. The white surface finish offered by Bradford's Thermoplast™ Decorative Facing Foil (990) makes it an ideal product for the facing of bulk insulation (i.e. Glasswool or Fibretex™ Rockwool) when used in commercial and residential building applications.

Product Description

Bradford Thermoplast™ Decorative Facing Foil (990) is a medium duty reflective foil laminate consisting of multiple layers of aluminium foil and kraft papers, with additional strength provided by fibreglass yarn in a tri-directional (three way) pattern, bonded together with flame retardant adhesive. Bradford Thermoplast™ Decorative Facing Foil (990) has a white surface finish on one side and is only supplied as a factory applied facing to CSR Bradford's range of bulk insulations.

Standard Sizes & Packaging

Width	Length	m ² per roll	Product Code
1350 mm	500 M	675	105495
1350 mm	1000 M	1350	105511

Accessories

When required to join or seal Bradford Thermoplast™ Decorative Facing Foil (990) it is recommended to use Bradford Thermoplast™ 990WFT Tape in either 72mm or 96mm widths.

Width	Length	Rolls per carton	Product Code
72 mm	50 M	16	106138
96 mm	50 M	12	106824

Health & Safety

Information on any known health risks and safe handling methods are available on our website:
www.bradfordinsulation.com.au

Applications

Bradford Thermoplast™ Decorative Facing Foil (990) is used as a facing for bulk insulation materials (i.e. Glasswool or Fibretex™ Rockwool). When installed under metal roofs and in walls, the white surface finish offered by Bradford's Thermoplast™ Decorative Facing Foil (990) presents to the inside of the building, making it an ideal facing material for use in sporting complexes, gymnasiums and warehouses where an aesthetically pleasing finish and good light diffusion is desired.

Benefits

- Highly durable and easy to handle on site
- Cost effective decorative lining
- Excellent facing carrier for bulk insulation (i.e. Glasswool or Fibretex™ Rockwool)
- Presents uniform decorative finish for wall and roof linings of stadiums, gymnasiums and warehouses

Durability / Warranty

Bradford Thermoplast™ Decorative Facing Foil (990) is guaranteed to be free from manufacturing defects and satisfies relevant Australian and New Zealand Building

THERMOPLAST™ DECORATIVE FACING FOIL (990)

Codes, when installed in accordance with AS / NZS 4200.2:1994 Pliable Building Membranes and Underlays, Part 2 Installation Requirements, including any special notes detailed in this data sheet or those found in associated Bradford documentation.

All work must be designed and constructed in compliance with all provisions in the current Building Code, regulations and relevant standards.

Being a secondary roof / wall lining material, Bradford Thermoplast™ Decorative Facing Foil (990) is not designed to withstand prolonged direct exposure to the elements, hence once installed, external cladding materials must be installed without delay.

Bradford Thermoplast™ Decorative Facing Foil (990) should be stored in a cool and dry place away from sunlight before use, and should not come in to contact with wet concrete or other alkaline based materials.

To ensure durability and maximum thermal performance is achieved, Bradford Thermoplast™ Decorative Facing Foil (990) should be installed to present a minimum of 40mm air space adjacent to the white surface.

Due to the nature of this product, the surface finish may not be completely smooth. Care must be taken when installing to avoid creasing as this may detract from the overall finish. If in doubt as to Bradford Thermoplast™ Decorative Facing Foil (990) suitability for a specific application, please contact your nearest CSR Building Products' office or your local representative.

Physical Properties

Classification in accordance with AS / NZS 4200.1:1994 unless otherwise stated.

Classifications

Criteria	Reference	Result
Duty Classification	Table 1-AS / NZS 4200.1:1994	Medium
Vapour Barrier	ASTM E96:2005	Medium
Emittance	AS / NZS 4201.5:1994	Reflective
Water Barrier	AS / NZS 4201.4:1994	High
Flammability Index	AS / NZS 1530.2:1993	≤ 5
Absorbency	AS / NZS 4201.6:1994	Unclassified
Resistance to Dry Delamination	AS / NZS 4201.1:1994	Pass
Resistance to Wet Delamination	AS / NZS 4201.2:1994	Pass
Tensile Strength	AS / NZS 1301.448:1991	
• Machine Direction (k/Nm)		≥ 9.5 kN / m
• Lateral Direction (k/Nm)		≥ 6.0 kN / m
Edge Tear Resistance	TAPPI T470:1980	
• Machine Direction (N)		≥ 65 N
• Lateral Direction (N)		≥ 65 N

Sample Specification

The insulation material shall be CSR Bradford's (*insert bulk insulation type, thickness and Rm value*) with CSR Bradford's Medium Duty Thermoplast™ 990 Decorative Facing Foil factory adhered to one side, which has been tested to AS / NZS 4200.1:1994 and AS / NZS 3837:1998 standards.

Where maximum resistance to penetration of water vapour is required all penetrations and the 150mm wide foil overlaps shall be sealed by means of CSR Bradford's 72mm wide Thermoplast™ 990WFT tape, applied in accordance with the manufacturer's recommendations.



CSR Bradford Insulation

55 Stennett Rd, Ingleburn NSW 2565 Australia.

Telephone (02) 9765 7000 **Facsimile** (02) 9765 7002

www.bradfordinsulation.com.au

CSR Bradford Insulation is a business division of CSR Building Products Limited ABN 55 008 631 356

The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Bradford Insulation. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the Bradford website for the latest version of this document. The purchaser should independently determine the suitability of the product for the intended use and application.