

# Anticon Tuff<sup>™</sup> with a tough polyweave backing **BUILD ON A TRUSTED NAME**

Over the years the name Anticon has gained a reputation as one of the most effective ways to control both temperature and condensation under metal roofs. Installation of Anticon directly under the metal roof sheet during construction will assist in meeting the mandatory energy efficiency requirements as set out in the Building Code of Australia. Now with the added benefit of improved puncture resistance, Anticon Tuff is available from CSR Bradford with the same assurance of quality and performance.

## THE KEY PERFORMANCE BENEFITS OF BRADFORD ANTICON

- Acoustic insulation: Reduce unwanted airborne noise such as aircraft or traffic and also provide a damping effect to reduce impact noise such as rain or hail
- **Thermal insulation:** Slow the heat gain in summer and reduce the loss of warmth from inside the home in winter
- **Condensation control:** Reduce the risk of the occurrence of condensation formation under your metal roof which can cause damage to plasterboard ceilings and mould growth
- **Fire performance:** Anticon's bulk insulation blanket is made from non-combustible fibres and meets the BAL (bushfire attack level) requirement for metal clad roofs in bushfire areas
- By reducing temperature variation, Anticon assists in minimising 'metal creeping noises' which can occur in buildings with metal components

## ADDITIONAL BENEFITS OF BRADFORD ANTICON TUFF

- Improved tear and puncture resistance
- Improved surface finish durability
- Easier to install with less resistance to unrolling



TEAR A RE

#### **BUILD IN THE ANTICON ADVANTAGE**

Installation is easy, but only before the roof sheet is laid.

# Bradford Anticon Tuff Metal roof Outdoor air film Bradford Gold Ceiling Batts Standard plasterboard (10mm) Indoor air-film (non-reflective surface)


# THE SENSITIVE CHOICE® IN INSULATION

CSR Bradford is the only approved insulation partner of the National Asthma Council Australia's Sensitive Choice<sup>®</sup> program. This program



CSR

recognises companies who develop products like Anticon and Gold Ceiling Batts, that may be better choices for people with asthma or allergies.



## ANTICON TUFF - THE NAME EVERYONE WILL LOOK UP TO

Available with either a medium duty (MD) or heavy duty (HD) facing, Anticon Tuff easily faces the tough jobs when higher levels of tear and puncture resistance are important. Combine Anticon Tuff with CSR Bradford's range of Gold ceiling batts to create higher levels of thermal and acoustic performance. The inclusion of Bradford roof vents and eave grilles can also provide further protection against peak summer temperatures, as well as additional condensation control. Please check with your building certifier to ensure that the system you choose meets the required energy efficiency targets and consult with Bradford for advice on condensation control.

### **PRODUCT & SYSTEM PERFORMANCE**

Product Name	Thickness (mm)	Base material R-Value	Dimensions (m x mm)	Area per pack (m <sup>2</sup> )	Winter R <sub>τ</sub> value (heat flow up)	Summer R <sub>T</sub> value (heat flow down)	Winter R <sub>T</sub> value (heat flow up)	Summer R <sub>T</sub> value (heat flow down)
Ventilated					Anticon only – no ceiling batts		Anticon + R3.5 Gold ceiling batts	
Anticon Tuff 60	60	R <sub>M</sub> 1.3	15 x 1200	18	R <sub>τ</sub> 1.9	R <sub>T</sub> 2.8	R <sub>τ</sub> 5.6	R <sub>τ</sub> 6.2
Anticon Tuff 80	80	R <sub>M</sub> 1.8	15 x 1200	18	R <sub>T</sub> 2.4	R <sub>T</sub> 3.3	R <sub>T</sub> 6.1	R <sub>τ</sub> 6.7
Anticon Tuff 100	100	R <sub>M</sub> 2.3	10 x 1200	12	R <sub>τ</sub> 3.0	R <sub>τ</sub> 3.8	R <sub>τ</sub> 6.7	R <sub>T</sub> 7.2
Non-ventilated					Anticon only – no ceiling batts		Anticon + R3.5 Gold ceiling batts	
Anticon Tuff 60	60	R <sub>M</sub> 1.3	15 x 1200	18	R <sub>T</sub> 2.1	R <sub>T</sub> 2.6	R <sub>⊤</sub> 5.8	R <sub>τ</sub> 5.9
Anticon Tuff 80	80	R <sub>M</sub> 1.8	15 x 1200	18	R <sub>T</sub> 2.7	R <sub>τ</sub> 3.0	R <sub>T</sub> 6.3	R <sub>τ</sub> 6.4
Anticon Tuff 100	100	R <sub>M</sub> 2.3	10 x 1200	12	R <sub>T</sub> 3.2	R <sub>τ</sub> 3.5	R <sub>T</sub> 6.9	R <sub>τ</sub> 6.9

Note: System based on an R0200 system with a 22° pitched metal roof. All R<sub>T</sub> values assume low emissivity (non-decorative) foil facing inward in attic space.

#### **IMPROVE THE ACOUSTIC PERFORMANCE OF YOUR ROOF**

Although the sound of gentle rain can be soothing, heavy rain or hail can be noisy and annoying. Installing Anticon directly under metal roofing can reduce the estimated sound power level of heavy rain by over 7%<sup>\*</sup>, improving the comfort of your environment. Anticon also reduces the transmission of aircraft noise through your metal roof, making your home environment more comfortable. \*0.48BMT Custom Orb

For more information or advice on the best system for your property, contact CSR Bradford on **1300 850 305** or visit **www.bradfordinsulation.com.au** 



**CSRBradford** 39 Delhi Road, North Ryde 2113 NSW Australia Telephone 1300 850 305 Facsimile (02) 9765 7002

Bradford Insulation is a business division of CSR Building Products Limited ABN 55 008 631 356. The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of Bradford Insulation. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the Bradford website for latest revision of this document. The purchaser should independently determine the suitability of the product for the intended use and application. B00034C