



Martini MSB

- **MSB** is designed to increase the acoustic performance of partition walls and ceilings in commercial applications.
- Non-irritant and does not require any protective clothing or masks during installation.
- Available in standard white colour. Black or grey available upon request.

Applications

MSB is ideal for use in plasterboard partition walls and suspended ceilings in offices and institutions such as education, healthcare and civic buildings. Installed in partition walls, MSB provides excellent sound transmission reduction and thermal performance, reducing heat transfer between rooms.

For specific acoustic applications refer to the Martini Acoustic Design Guide.

Acoustic performance

A performance increase of up to 9 R_w points can be achieved with the inclusion of **MSB** in the wall cavity. An increase of one R_w point is equivalent to a reduction of one decibel in sound transmission. For more detailed information refer to the Martini Acoustic Design Guide.

Typical plasterboard wall system comprising 13mm standard plasterboard either side of steel studs at 64mm

MSB 2	MSB 3	MSB 4	MSB 5
R_w 41, $R_w + C_{tr}$ 33	R_w 41, $R_w + C_{tr}$ 33	R_w 42*	R_w 43*

Typical plasterboard wall system comprising 13mm fire rated plasterboard either side of steel studs at 64mm

MSB 2	MSB 3	MSB 4	MSB 5
R_w 44, $R_w + C_{tr}$ 35	R_w 44, $R_w + C_{tr}$ 35	R_w 44*	R_w 45*

*Acoustic performance based on empirical data and expert opinions

Thermal performance

MSB 2	MSB 3	MSB 4	MSB 5	MSB 6
R 0.8*	R 1.0*	R 1.2*	R 1.4*	R 1.7*

*Calculated value

Environmental benefits

MSB is manufactured from thermally bonded polyester fibre with up to 80% recycled fibre content from post-consumer PET packaging, such as empty drink bottles. The product is 100% recyclable and has very high reuse potential as insulation. CSR Martini's Product Stewardship Program can be viewed at www.csrmartini.com.au.

- No chemicals or resin binders are used in manufacture.
- Odourless and contains no harmful volatile organic compounds (VOC).
- No waste is generated in manufacture.
- No water or ozone-depleting gases are used in manufacture.
- No chlorides are present in the product.
- Suitable for use in Green Star™ projects.

www.csrmartini.com.au





Pack specifications

Product	Recovered thickness (mm)*	Size (m x mm)	Rolls per pack	m ² per pack	Product Code
MSB2	50	16.3 x 450	3	22.0	127818
MSB2	50	16.3 x 610	2	19.8	126343
MSB3	65	16.3 x 450	3	22.0	127819
MSB3	65	16.3 x 610	2	19.8	126344
MSB4	75	16.3 x 450	3	22.0	127820
MSB4	75	16.3 x 610	2	19.8	126345
MSB5	85	13.6 x 450	3	18.3	127821
MSB5	85	13.6 x 610	2	16.5	126346
MSB6	100	13.6 x 450	2	12.2	129187
MSB6	100	13.6 x 610	2	16.5	126347

*Product thickness recovery time can vary depending on length of time in compressed packaging and air temperature.

Physical description and properties

Volatiles:	Nil		
Specific Gravity:	1.38		
Flash Point:	None allocated		
Other Properties:	Non-allergenic, low irritant, low flame response, resilient		
Ingredients:	Organic, long chain synthetic polymer		
Max Service Temp:	150°C		
Alkalinity:	pH 7.8 (pH 7 is neutral)		
Moisture Absorption:	Exposure to an atmosphere of 50°C & 95% RH for four days gives moisture absorption of less than 0.2% by volume		
Fire Resistance:	The following results were obtained when CSR Martini product was subjected to early fire hazard testing in accordance with Australian Standards AS 1530.3.	Ignitability	0
		Spread of Flame	0
		Heat Evolved	0
		Smoke Developed	0-1

Disclaimer: The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Martini. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the CSR Martini website for the latest version of this document. The purchaser should independently determine the suitability of the product for the intended use and application.

www.csrmartini.com.au

Distributed by:



CSR Bradford
Locked Bag 1345 North Ryde BC NSW 1670
csrbradford.com.au
Email: bradfordenquiries@csr.com.au

For further information
call **1300 850 305** or
visit bradfordinsulation.com.au

CSR