

The Right Wrap

Enviroseal™ is a highly vapour permeable wall wrap that is compatible behind brick veneer, FC sheet, timber and metal cladding systems. Including; James Hardie™, Weathertex, Cemintel® and Hebel® products.

Enviroseal ProctorWrap – The Right Wrap for use behind residential Brick Veneer and all Lightweight Clad systems.

The Enviroseal™ ProctorWrap™ range of products is compatible with all timber and metal Lightweight Clad systems, including; James Hardie™, Weathertex and Cemintel® and Hebel® products.

- **Minimises Risk of Condensation Related Rectification Work** – Enviroseal is vapour permeable and allows moisture to escape the wall and help reduce risk of condensation
- **Improves Speed of Construction** – Allow tradies to access the site immediately after wrapping and prevent delays caused by bad weather
- **Improves Air Tightness and Energy Efficiency** – Wrapping reduces draughts and minimises energy consumption
- **A Tough Weather Barrier** – Protects the building frame from decay by reducing the entry of wind driven rain and dust.

Application Summary

CONSIDERATION	RECOMMENDED FOR:
Wall Construction	Brick Veneer and all Lightweight Clad
Insulation Type	Highly recommended when using R2.0 batts or above
External Environment	Warm to Cold

Note: Bradford Enviroseal is not suitable for tropical climates. Tropical climates require a Vapour Barrier 'High' and the use of Bradford Thermosteal Wall Wrap is recommended.



Enviroseal™ ProctorWrap™ is suitable for use behind both brick veneer and lightweight clad walls. Enviroseal™ ProctorWrap™ is classified as a water barrier and is a vapour permeable wall wrap in accordance with AS/NZS 4200.1.

JAMES HARDIE	WEATHERTEX	CEMINTEL	HEBEL
Enviroseal ProctorWrap exceeds the membrane specification published in the James Hardie documentation for use with these cladding systems:	As per the Weathertex cladding installation manual, Enviroseal ProctorWrap is a recommended vapour permeable membrane product for all Weathertex external wall systems, including:	Enviroseal ProctorWrap is compatible with Cemintel cladding products including:	As per the Hebel Design and Installation Guide, Enviroseal ProctorWrap is compatible with the following facades:
<ul style="list-style-type: none"> ✓ Scyon™ Stria™ Cladding ✓ Scyon™ Matrix™ Cladding ✓ Scyon™ Linea™ Weatherboard ✓ Scyon™ Axon™ Cladding ✓ PrimeLine® Weatherboard ✓ PanelClad® Sheet ✓ HardieTex™ Blue Board System ✓ HardiePlank® Weatherboard ✓ HardieFlex™ Sheet ✓ ExoTec® Facade Panel ✓ EasyLap™ Panel ✓ ComTex® Fixing System 	<ul style="list-style-type: none"> ✓ Selflok Texwood ✓ Selflok Old Colonial Smooth ✓ Selflok Millwood ✓ Selflok Millwood Ruff ✓ Selflok Ecogroove Woodsman ✓ Selflok Ecogroove Smooth ✓ Primelok Woodsman ✓ Primelok Smooth ✓ Primelok Shadowood Smooth ✓ Primelok Ruff Sawn ✓ Primelok Federation Smooth ✓ Primelok Federation Ruff ✓ Classic Smooth ✓ Classic Rusticated Smooth ✓ Classic Rusticated Ruff ✓ Classic Ruff Sawn 	<ul style="list-style-type: none"> ✓ Barestone™ ✓ Commercial Express Panel® ✓ Mosaic® ✓ Scarborough® Weatherboard ✓ Endeavour® Weatherboard ✓ Woodgrain Plank ✓ Surround™ Cladding ✓ Territory™ Cladding ✓ Aspect Cladding® ✓ Cladding Sheet ✓ Edge Cladding ✓ Headland® Weatherboard ✓ Commercial Rendaline® ✓ SimpleLine® 	<ul style="list-style-type: none"> ✓ Power Panel ✓ Power Panel XL



For further information Call **1300 850 305** or visit **bradfordinsulation.com.au**

CSR Bradford Locked Bag 1345 North Ryde BC NSW 1670
bradfordinsulation.com.au

CSR Bradford is a business division of CSR Building Products Limited ABN 55 008 631 356
The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Bradford. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the CSR Bradford website for the latest revision of this document. The purchaser should independently determine the suitability of the product for the intended use and application.

