

FIRESEAL PARTY WALL BATTEN FILLERS

SKU Table

Roof Profile Height (mm)	Length Per Piece (mm)	Pieces per Pack	Lineal meter per pack	Product Code
40	100	35	4	125418

Standard packaging is cardboard box

Physical Properties

Density		70kg/m ³				
Fusion Temperature		In excess of 1150 °C				
Thermal Conductivity		0.037W/mK at 23 °C mean temperature.				
Non Combustibility	AS/NZS1530.1:1994	Non-Combustable				
Fire Hazard Properties	AS/NZS 1530.3:1999	<ul style="list-style-type: none"> • Ignitability: 0 • Spread of flame 0 • Heat Evolved 0 • Smoke Developed 0 				
Corrosion Resistance	BS 3958 part 5- 1969	pH 7.0-9.0; Less than 20ppm soluble chlorides;				
Moisture Absorption	When placed in a controlled atmosphere of 50°C and 95% relative humidity for 96 hours.	Less than 0.2% by volume.				
Fire Protection Level		<table border="1"> <thead> <tr> <th>Thickness of Fireseal (mm)</th> <th>Level of Fire Protection (minutes)</th> </tr> </thead> <tbody> <tr> <td>40</td> <td>-/180/180</td> </tr> </tbody> </table>	Thickness of Fireseal (mm)	Level of Fire Protection (minutes)	40	-/180/180
Thickness of Fireseal (mm)	Level of Fire Protection (minutes)					
40	-/180/180					

