

THERMO REFLECTIVE PRODUCTS

PRODUCT DESCRIPTION

Polyair Performa XHD is classified under AS/NZS 4859.1:2002/Amdt.1 as a reflective insulation material (and sarking AS/NZS 4200.1/.2) and falls into the Group 1 category of section 9.2 of the standard. Polyair Performa XHD is manufactured with two external layers of extra strong reflective aluminium foils with the external layer coated in a special antiglare that can reflect up to 95% of the sun's radiant heat. Polyair Performa XHD incorporates a foam structure that reduces heat transfer from the antiglare outer foil surface to the inner silver foil surface. Polyair Performa XHD is available in 4mm and 8mm thicknesses.

SPECIFICATION TABLE

| | THICKNESS (mm) | ROLL SIZE (m x mm) | m ² PER ROLL (m ²) | ROLL DIAMETER (mm) | ROLL WEIGHT (kg) | PRODUCT CODE |
|------------------|----------------|--------------------|---|--------------------|------------------|--------------|
| Performa 4.0 XHD | 4 (+/- 0.5) | 22.25 x 1350 | 30 | 410 | 13 | 152161 |
| Performa 4.0 XHD | 4 (+/- 0.5) | 40 x 1350 | 54 | 560 | 19 | 152429 |
| Performa 8.0 XHD | 8 (+/- 0.5) | 22.25 x 1350 | 30 | 520 | 16 | 152472 |

APPLICATIONS

Polyair Performa XHD can be used in a range of BCA classified buildings and in BAL effected regions. It can be used in a range of residential applications including tiled roofs, steel roofs, brick veneer walls and some light weight clad walls. For advice on the suitability of these products for your project contact the Bradford technical services team on 1300 850 305.

INSTALLATION GUIDANCE

- Install with antiglare surface facing outwards.
- Sealing overlaps, penetrations and damaged areas with a reinforced aluminium foil tape (or approved self-adhesive strip) is recommended especially when aiming to achieve a consistent: stated thermal performance, seal against draughts, seal against vapour infiltration, seal against water entry into the building.
- Overlaps should be a minimum 50mm when a reinforced aluminium foil tape (or approved self-adhesive strip) is used.
- Overlaps should be a minimum of 150mm if no tape is used.
- Follow all relevant OHS and statutory regulations – eye protection from sun glare is recommended.

THERMAL BREAK

The BCA Volumes 1 and 2 outline the requirement to reduce thermal bridging of direct-fix claddings* onto metal frames by installing a thermal break with an R-Value of not less than R_m 0.2, positioned between the lightweight external cladding* and the primary metal framing. Polyair Performa 8.0 XHD is a continuous reflective insulation material and achieves an uncompressed R-Value of R_m 0.2 in accordance with AS/NZS4859.1, which is also a requirement of the BCA.

*Cladding includes: metal sheeting, weatherboards, fibre-cement or similar

RADIANT
HEAT BARRIER
AND EXTRA
HEAVY DUTY
SARKING
IN ONE

Polyair Performa XHD – Thermo Reflective Products

CLASSIFICATIONS

| PROPERTY | REFERENCE | RESULT |
|--------------------------------|---|--|
| Emittance | AS/NZS 4201.5:1994/ASTM E408 | Double-sided reflective Antiglare (outer face) E0.05 Silver (inner face) E0.03 |
| Material thermal resistance | ASTM C518 as part of AS/NZS 4859.1:2002/Amdt.1 | R _m 0.10 Performa 4.0 XHD R _m 0.20 Performa 8.0 XHD |
| Duty | Table 1 – AS/NZS 4200.1:1994 | Extra heavy duty |
| Vapour barrier | ASTM E96 | Medium |
| Water barrier | AS/NZS 4201.4:1994 | High |
| Absorbency | AS/NZS 4201.6:1994 | Unclassified |
| Shrinkage | AS/NZS 4201.3:1994 | <0.5% |
| Resistance to dry delamination | AS/NZS 4201.1:1994 | Pass |
| Resistance to wet delamination | AS/NZS 4201.2:1994 | Pass |
| Surface corrosion | AS/NZS 4859.1:2002 | Pass |
| Flammability index | AS 1530.2 | Low (≤5) |
| Early fire hazard Indices | AS/NZS 1530.3 | |
| Ignitability | AS/NZS 1530.3 | 0 |
| Spread of flame | AS/NZS 1530.3 | 0 |
| Heat evolved | AS/NZS 1530.3 | 0 |
| Smoke developed | AS/NZS 1530.3 | 2 |



TOTAL R-VALUE PERFORMANCE WITH POLYAIR PERFORMA 4.0 XHD

| PITCHED METAL ROOF (Attic cavity ventilated*) | PITCHED TILED ROOF (Attic cavity ventilated*) | BRICK VENEER WALL | LIGHTWEIGHT CLAD WALL | SHED ROOF |
|--|--|---|---|---|
| Heat flow in (summer) = R _t 2.4 | Heat flow in (summer) = R _t 2.1 | Heat flow in (summer) = R _t 1.9 | Heat flow in (summer) = R _t 1.7 | Heat flow in (summer) = R _t 1.6 |
| Heat flow out (winter) = R _t 1.1 | Heat flow out (winter) = R _t 1.0 | Heat flow out (winter) = R _t 2.0 | Heat flow out (winter) = R _t 1.8 | Heat flow out (winter) = R _t 0.8 |

Total R-Value results are based on Polyair Performa 4.0 XHD. Add R0.1 to each result if using Polyair Performa 8.0 XHD.

Pitched metal roof system comprises of: metal roof 22.5°, 40mm airspace, Polyair Performa 4.0 XHD (with slight dust cover), ventilated airspace, 10mm plasterboard ceiling. Pitched tiled roof system comprises of: pitched roof 22.5°, 40mm airspace, Polyair Performa 4.0 XHD (with moderate dust cover), ventilated airspace, 10mm plasterboard ceiling. Brick veneer wall system comprises of: 110mm brick, 35mm airspace, Polyair Performa 4.0 XHD, 90mm airspace, 10mm plasterboard. Lightweight clad wall system comprises of: lightweight cladding, 35mm airspace, Polyair Performa 4.0 XHD, 90mm airspace, 10mm plasterboard. Shed metal roof comprises of: metal roof 11°, 40mm airspace, Polyair Performa 4.0 XHD (with slight dust cover).

*Ventilated attic space based on incorporating minimum 2x wind driven ventilators such as Edmonds WindMaster 300mm throat ventilator (total aggregate area 0.14m²) in conjunction with eave vents of not less than 0.2% of the plan ceiling area. Refer to explanation in the BCA 3.12.1.2(b)(ii).

TOTAL R-VALUE ASSUMPTIONS

The contribution of this product to a Total R-Value depends on the installation and environmental conditions. The Total R-Value will be reduced in the event of the accumulation of dust on upward facing surfaces and in those cavities that are ventilated.

Thermal calculations are based on Australian parameters and in accordance with AS/NZS 4859.1:2002/Amdt.1. The contribution of this product towards the Total R-Value depends on installation and environmental conditions. For upward facing surfaces of horizontal or sloping reflective insulation in non-vented cavities where no special precautions for prevention of dust ingress have been included, the Total R-Value is calculated based on an emittance for the case of slight dust cover in accordance with AS/NZS4859.1 Paragraph K3.2(a)(ii), unless otherwise stated. For calculation purposes, the air gaps are assumed as still parallel air gaps unless otherwise stated and the membrane continuous.

SAFETY INSTRUCTIONS

Polyair is safe to handle, no protective clothing, gloves or mask is required. It is the responsibility of the installer to observe and comply with all relevant OHS and statutory regulations. Read electrical safety warning (below).

ELECTRICAL SAFETY WARNING

This product contains aluminium foil which conducts electricity. To avoid electrocution, care should be taken to ensure that this product or conductive fasteners used to secure this product, do not come into contact or close proximity with electrical wiring during installation or use. This product should not be installed in an existing structure in a horizontal orientation such as a ceiling or sub-floor application due to the presence of electrical wiring in the framing.



CSR Bradford
Locked Bag 1345 North Ryde BC NSW 1670
csrbradford.com.au
Email: bradfordenquiries@csr.com.au

For further information
call **1300 850 305** or
visit reflectiveinsulation.com.au



CSR Bradford is a business division of CSR Building Products Limited ABN 55 008 631 356

The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Bradford. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the CSR Bradford website for the latest revision of this document. The purchaser should independently determine the suitability of the product for the intended use and application.